



101 / 102007 / 00000

GB 04/003083



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

REC'D 27 AUG 2004

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


Signed

Andrew Gersey

Dated

20 August 2004





18JUL03 E823512-1 D02903
P01/7700 0.00-0316803.6

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

11292P5 GB/JM

2. Patent application number

(The Patent Office will fill in this part)

0316803.6

18 JUL 2003

3. Full name, address and postcode of the or of each applicant (*underline all surnames*)

Reckitt Benckiser (Australia) Pty Limited
44 Wharf Road
West Ryde
NSW 2114
Australia

Patents ADP number (*if you know it*)

07954 431001 ✓

If the applicant is a corporate body, give the country/state of its incorporation

Australia

4. Title of the invention

Portable Device for Enabling Vapour Emanation

5. Name of your agent (*if you have one*)

"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)

John Crawford McKNIGHT
Reckitt Benckiser plc
Group Patents Department
Dansom Lane
Hull
HU8 7DS
United Kingdom

Patents ADP number (*if you know it*)

~~07800 303001~~

7799521001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country

Priority application number

Date of filing

(*if you know it*) (day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*

Yes

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 6 /

Claim(s) 3 /

Abstract 1 /

Drawing(s) 3 + 3 92

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

One

Request for substantive examination (Patents Form 10/77)

One

Any other documents (please specify)

FS1

11.

I/We request the grant of a patent on the basis of this application.

Signature

John Crawford McKNIGHT

Date

16 July 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

John Crawford McKNIGHT 01482 583719

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Portable Device for Enabling Vapour Emanation

Field of the Invention

This invention relates to a device, particularly a portable device, that provides
5 for the emanation of a chemical formulation, such as an insecticide or a fragrance, into a surrounding atmosphere.

Background to the Invention

A number of patent documents disclose portable devices that enable the
10 application of a herbicide or an insecticide, particularly for the purpose of killing weeds and the like. Such an example is disclosed in US Patent No 4,309,842 in which a portable hand-held herbicide and insecticide applicator comprises a tube 12 which acts as a handle and connected at one end of the handle is a pair of hollow prong sections. The prong sections together with the handle 12 form a liquid reservoir conduit for the
15 pesticide or herbicide and extending between the ends of the prong sections is an absorptive rope mop which is saturated with the liquid pesticide or herbicide. The user then drags the device over weeds and the like such that the saturated rope mop comes into contact with the weeds and thereby eventually kills the weeds.

Other devices include sprayer systems that have a reservoir and use an electric
20 motor, such as is disclosed in US Patent No 6,109,548. This sprayer system reduces the need to manually create pressure within a portable spray unit. A valve stem within the reservoir may be utilised by a user to connect a conventional air tank thereto for inserting high amounts of air pressure directly into the reservoir without requiring the use of a manual or electric pump. Where a power switch is closed the electric motor
25 operates the air compressor whenever the air pressure within the reservoir drops below a predetermined level. A manual pump may be utilised when the electric pump fails or a battery connected to the electric motor becomes discharged.

Other systems involve the atomisation of liquids, such as is disclosed in US
Patent No 4,356,528. This patent discloses an invention that utilises electrostatic
30 spraying of liquid compositions, particularly over leaves of plants, by supplying a liquid to a spray orifice, which is preferably of capillary dimensions. The spray orifice preferably has a charged surface which is electrically conducting or semi-conducting and which is adjacent a field intensifying electrode, the arrangement being such that the liquid is drawn out primarily by electrostatic forces, atomised into electrically charged

particles and projected past the electrode. Thus the particles wrap around the leaves of the plants and coat both upper and lower surfaces of the leaves.

None of the above prior art systems provide a portable, substantially low cost personal device that enables the discharge into surrounding atmosphere of a chemical formulation, particularly for the purpose of a personal insect repellent or in situations where a portable small device may be used in a room which periodically enables the emanation or vaporisation of the chemical formulation. There is a need for such a device that is substantially low cost to run, may be run on batteries and last a substantial length of time without having to replace batteries or provide a new or refilled reservoir of the chemical formulation.

The present invention has substantial advantages over the above mentioned applicators and sprayers and conventional aerosol sprayers as there is no need for the user to physically operate the device as it may be left in an area to automatically discharge a chemical vapour into a surrounding atmosphere.

Summary of the Invention

According to a first aspect of the invention there is provided a device for enabling vapourization of a chemical formulation into an atmosphere comprising:
means for receiving a cartridge including the chemical formulation;

aperture means to enable vapourized chemical formulation to be guided therethrough into the atmosphere;

wherein the chemical formulation contacts a heater means in order to vapourize the chemical formulation.

Preferably the receiving means is a recess having an opening at one side of the device.

The recess may have guide means for guiding the cartridge therethrough.

The recess or guide means may have projection means, preferably in the form of lugs, that provide an interference fit with corresponding indentation means on the cartridge in order to locate the cartridge in a fixed relationship with respect to the heater means.

Alternatively the recess or guide means may have indentation means, preferably in the form of notches, that provide an interference fit with corresponding projection means on the cartridge in order to locate the cartridge in a fixed relationship with respect to the heater means.

The device may include electrical circuit means in order to provide one or more pulses sequentially to the heater means in order to provide heat to the heater means to

vapourize the chemical formulation. The device may have compartment means to accommodate a power supply, preferably in the form of batteries, in order to provide power to the electrical circuit means.

The device may further comprise a partition that divides the interior of the device into a first compartment and a second compartment. The partition may comprise an electrical circuit board housing an electrical circuit means. The electrical circuit board may be double-sided providing electrical connections to electrical components of the electrical circuit means. The electrical components may be located on one or both sides of the electrical circuit board. The device may incorporate the heater means and the heater means may be mounted on a side of the electrical circuit board within the first compartment, the first compartment preferably housing the receiving means and having the aperture means so as to enable the heater means to contact the chemical formulation.

The device may be constructed as two detachable members, a first or top member housing the receiving means and aperture means, and a second or base member preferably housing the electrical circuit means and power supply. Alternatively the device may be constructed as a single article. The heater means is preferably in the form of a microheater element and more particularly in the form of an impedance means such as a resistor. Alternatively, the first and second members may be divided by a partition forming an electrical circuit board for the electrical circuit means. Preferably the electrical circuit board for the electrical circuit means is double-sided and has mounted on one side the heater means such that the heater means is in communication with components of the electrical circuit means on the opposite side, but protrudes into the top member to enable contact with the chemical formulation, preferably through a wick means. Alternatively, some or all of the components of the electrical circuit means, such as an indicator means and switch means, are located on the same side of the electrical circuit board, preferably on the side protruding into the top or first member.

The device may have a switch means to activate and deactivate the power supply and therefore the emanation of the chemical formulation. The device may further have indicator means to indicate battery charge status and/or device failure.

Brief Description of the Drawings

Preferred embodiments of the invention will hereinafter be described, by way of example only, with reference to the accompanying drawings wherein:

Figure 1 is a perspective view of a device in accordance with the present invention;

Figure 2 is an underneath view of the device of Figure 1 with a member cover removed;

5 Figure 3 is a plan view of the device of Figure 2;

Figure 4 is an end view of the device of Figure 1; and

Figure 5 is a cross sectional side view of the device of Figure 1 showing guide means for a cartridge.

10 Detailed Description of Preferred Embodiments

Shown in Figure 1 is a portable device which may be carried by a user or placed in for example a room or some other location. The device comprises a first or top member 2 and a second or bottom member 1. The second member 1 houses a pair of batteries 7 and an electrical circuit board 8 which is mounted flush with the top surface
 15 of the member 1. The electrical or printed circuit board 8 may be double-sided and form a partition or dividing panel between the first member 2 and the second member 1. Electrical components forming an electrical circuit means may be located on one, the other or both sides of the board 8. It is to be noted that the device in an alternative arrangement may be constructed in a single piece such as through injection moulding
 20 rather than two separate members 1 and 2. In one embodiment, all electronic components and connections are mounted on the lower side of the circuit board 8, in other words within or facing the interior of the member 1, and a heater means 11 is located on the upper side of the electrical circuit board 8 mounted flush with the upper or top surface, such that the heater means 11 protrudes into member 2 to be in contact
 25 with the chemical formulation. In another embodiment, the heater means 11, a switch 6 and an indicator 5 are mounted on the same side of the electrical circuit board 8. Where the device is a singular construction or formed of two detachable members 2 and 1, a partition forming either a single or double-sided electrical circuit board 8 may divide the device into two compartments. The first compartment may house a recess or
 30 receiving means (see Figures 4 and 5) and have apertures 3 while the second compartment houses the power supply 7. The heater means 11 is preferably in the form of a microheater element and more particularly an impedance means such as a resistor. The batteries 7 supply power to the electrical circuit board components which in turn deliver a series of pulses to the heater means 11 in order to heat the heater means 11.
 35 The batteries are mounted in such a manner that the positive end of the battery 7 connects with a positive battery terminal 9 and the negative end of the battery connects

with a negative battery terminal 10. Typically AA batteries are used but any other form or size of batteries may be used, such as AAA batteries.

The lower member 1 also has a switch means 6 used to turn a device on and off and to allow the user control or provide additional bursts of vapour when initially
5 turning the unit on. Alternatively there may be a further mode, such as a high burst mode, which the user can move the switch to in order to provide additional bursts of vapour. Pulses may be supplied to the heater means 11 via a suitable power supply.

Also shown adjacent the switch means 6 is an indicator 5 to provide an indication to the user where for example the resistor or microheater element 11 burns
10 out or where the batteries are running low. When used to indicate the resistor 11 burning out or having some other fault, the indication might be provided by the light not turning off if a high resistance is sensed. A battery OK indicator may be instituted by using a LED indicator turning on for some seconds, then off, or beeping if the
15 battery is satisfactory. Alternatively the indicator may be used as a LED or a buzzer or an indication scheme analogous to car indicator lights, for example, a correct device operation as indicated by ON for several seconds then OFF when device is first turned on. Failure to light means battery failure and failure to go OFF means the device or resistor has failed in some manner. All of these indicators are necessary as the effect of the product is invisible in terms of the fragrance or insecticide being released and, as it
20 is also inaudible the only indication of a flat battery or a blown microheater element 11 will mean that the consumer suffers bites or is not aware of any fragrance.

The first member 2, which may be detachable from the lower or first member 1, has a series of apertures 3, forming a vent, and an opening 4 for receiving a cartridge type device which provides the insecticide or fragrance. Specifically the cartridge has a
25 reservoir which contains the insecticide or fragrance and has a wick means which is in constant contact with the insecticide or fragrance such that the chemical formulation is transferred through the wick from one end to the other end of the wick, with the other end of the wick being in contact with a microheater element. Such a cartridge device is described in a copending patent application to the present applicant. When the heater
30 element heats up it thereby vaporises the chemical formulation in the wick means in the vicinity of the heater and is dispersed through the series of apertures 3 into the surrounding atmosphere. The opening 4 provides entry to a recess which has guides 12 on either side of the recess (see Figures 4 and 5), into which the edges of the cartridge fit thereby guiding the cartridge through the recess towards the inner end of the recess.
35 Adjacent the end of the recess is located the microheater element 11. The recess additionally has a pair of projections or lugs, one on each side, that provide an

interference fit with corresponding notches or indentations in the cartridge, one on each side. Once the notches fit with the lugs it provides an indication to the user, through tactile feedback, that the cartridge is correctly located such that the wick means is in direct contact with the microheater element 11. Release of the vapour from the cartridge is provided through a pair of apertures located either side of the wick means in the vicinity of the microheater element 11. Alternatively, the recess may have a pair of notches or indentations, one on each side, that interference fit with a corresponding pair of projections or lugs, one on each side, on the cartridge.

Thus in use the cartridge is inserted by the user through the opening 4 and into the recess via the guide means 12, which may incorporate the aforementioned lugs or notches (not shown), or the device may already be fitted with such a cartridge having a refill pack housing the chemical formulation. The user then turns the device on through the switch means 6 and may initiate a burst mode to provide additional bursts of the vapour through the vents 3. The use may be for instant personal use or be left by the user in a room, such as a bedroom, switched on in situations where insecticide is to be dispersed at regular intervals into the room over a set period of hours. The device may have a clip to be attached to a user's clothing or belt or the like. Once an indication is provided to the user through the indicator 5 that the battery is low or the microheater element is faulty then the user simply replaces the batteries or the heater element. A user may regularly check that enough chemical formulation is stored in the reservoir and if it is low or there is no formulation left then it is simply a matter of removing the cartridge from the device and replacing it with a refill cartridge, or alternatively, refilling the present cartridge reservoir.

It will be appreciated by persons skilled in the art that numerous variations and/or modifications may be made to the invention as shown in the specific embodiments without departing from the spirit or scope of the invention as broadly described. The present embodiments are, therefore, to be considered in all respects as illustrative and not restrictive.

CLAIMS:

1. A device for enabling vapourization of a chemical formulation into an atmosphere comprising:
5 means for receiving a cartridge including the chemical formulation;
aperture means to enable vapourized chemical formulation to be guided therethrough into the atmosphere;
wherein the chemical formulation contacts a heater means in order to vapourize the chemical formulation.
- 10 2. A device according to claim 1 wherein the receiving means is a recess having an opening at one side of the device.
3. A device according to claim 2 wherein the recess has guide means for guiding
15 the cartridge therethrough.
4. A device according to claim 3 wherein the recess has projection means that provide an interference fit with corresponding indentation means on the cartridge in order to locate the cartridge in a fixed relationship with respect to the heater means.
20 5. A device according to claim 3 wherein the recess has indentation means that provides an interference fit with corresponding projection means on the cartridge in order to locate the cartridge in a fixed relationship with respect to the heater means.
- 25 6. A device according to claim 4 or claim 5 wherein the indentation means is one or more notches.
7. A device according to claim 4 or claim 5 wherein the projection means is one or more lugs.
- 30 8. A device according to claim 1 incorporating the heater means.
9. A device according to claim 8 further comprising electrical circuit means in order to provide one or more pulses sequentially to the heater means in order to provide
35 heat to the heater means to vapourize the chemical formulation.

10. A device according to claim 9 wherein a partition divides the interior of the device into a first compartment and a second compartment.

11. A device according to claim 10 wherein the partition comprises an electrical
5 circuit board housing an electrical circuit means.

12. A device according to claim 11 wherein the electrical circuit board is double-sided providing electrical connections to electrical components of the electrical circuit means.

10

13. A device according to claim 12 wherein the electrical components of the electrical circuit means are located either on one or both sides of the electrical circuit board.

15 14. A device according to claim 13 wherein the heater means is mounted on a side of the electrical circuit board within the first compartment, the first compartment housing the receiving means and having the aperture means so as to enable the heater means to contact the chemical formulation.

20 15. A device according to claim 9 constructed as two detachable members wherein a first member houses the receiving means and having aperture means and a second member houses a power supply.

25 16. A device according to claim 15 wherein the electrical circuit means is mounted on an electrical circuit board acting as a partition between the first member and the second member.

17. A device according to claim 16 wherein the electrical circuit board is double-sided.

30

18. A device according to claim 17 wherein the heater means is mounted on a side of the electrical circuit board in the first member to enable the heater means to contact the chemical formulation.

35 19. A device according to claim 14 or claim 18 wherein contact between the heater means and the chemical formulation is through a wick means.

20. A device according to claim 19 further comprising switch means to activate and deactivate the power supply.

21. A device according to claim 20 further comprising indicator means to indicate
5 battery charge status and/or device failure.

ABSTRACT**Portable Device for Enabling Vapour Emanation**

- 5 A device for enabling vapourization of a chemical formulation into an atmosphere comprising means for receiving a cartridge including the chemical formulation, aperture means (3) to enable vapourized chemical formulation to be guided therethrough into the atmosphere, wherein the chemical formulation contacts a heater means (11) in order to vapourize the chemical formulation.




Figure 1




Figure 3




Figure 2




Figure 4




Figure 5

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.